



PRODUCT TECHNICAL SPECIFICATION
CORAL VITRO – CV400HL

FCP_034_03_EN-01



DESCRIPTION:

Tank for domestic hot water (DHW) **STORAGE-PRODUCTION**.

For vertical installation on floor. Manufactured in **VITREOUS ENAMELLED STEEL** according to the DIN4753 standard, with mould-injected rigid **PU THERMAL INSULATION** and external PVC lining with zip closure. Tank includes an internal **HIGH PERFORMANCE** enamelled steel **COIL** for thermal exchange. Cathodic protection based on magnesium anodes.

Equipped with side opening for inspection / cleaning tasks, or to allocate a backup electric heating element (optional).

Includes also a sensor pocket on upper connections plate and control panel type "T" (with thermometer).

MAIN CHARACTERISTICS

Total capacity:	Total	400	L
Maximum working pressure:	Primary / Secondary	25 / 8	bar
Maximum working temperature:	Primary / Secondary	200 / 90	°C
Exchange surface:	Coil	4.8	m ²
Connections:	kv: primary inlet	1	" F
	kr: primary outlet	1	" F
	ww: DHW outlet	1	" M
	kw / e: cold water inlet / drain	1	" M
	z: recirculation	1	" M
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	88	W
External dimensions:	D: Diameter	770	mm
	H: Height (without connections)	1475	mm
	Diagonal (without connections)	1600	mm
Packaging dimensions:	Width / Height	820 / 1920	mm
Weight:	Without packaging / With packaging	174 / 185	kg