
## DHW PRODUCTION AND STORAGE TANKS CORAL VITRO - **STORAGE**

## lapesa



PRODUCT TECHNICAL SPECIFICATION CORAL VITRO – **CV300R** 

FCP\_038\_02\_EN



## **DESCRIPTION:**

Tank for domestic hot water (DHW) **STORAGE**.

For vertical installation on floor. Manufactured in **VITREOUS ENAMELLED STEEL** according to the DIN4753 standard, with mould-injected rigid **PU thermal insulation** and external PVC lining with zip closure. Cathodic protection based on magnesium anodes.

Equipped with side opening for inspection / cleaning tasks, or to allocate a backup electric heating element (optional). Includes sensor pocket on upper connections plate and control panel type "T" (with thermometer).

М	AIN CHARACTERISTICS		
Total capacity:	Total	300	L
Maximum working pressure:		8	bar
Maximum working temperature:		90	°C
Connections:	ww: DHW outlet	1	" M
	kw / e: cold water inlet / drain	1	" M
	z: recirculation	1 1⁄4	" M
	eh: plate exchanger connection	1 1⁄4	" M
	m: side connection	3/4	" M
Energy efficiency:	ErP Class	В	
	Static heat losses acc. to EN12897	67	W
External dimensions:	D: Diameter	620	mm
	H: Height (without connections)	1685	mm
	Diagonal (without connections)	1796	mm
Packaging dimensions:	Width / Height	680 / 1940	mm
Weight:	Without packaging / With packaging	79 / 88	kg



