



PRODUCT TECHNICAL SPECIFICATION
GEISER INERTIA – G1500L

FCP_051_03_EN-01



DESCRIPTION:

Carbon steel **BUFFER TANK**, for heating or cooling circuits, with integrated **STRATIFICATION SYSTEM**. For vertical installation on floor. Tank includes rigid mould-injected **PU thermal insulation**. Optionally, a kit of external padded PVC lining with zip closure, to be supplied in separate packaging unmounted. Tank also includes one side threaded connection for an optional electrical heating element.

MAIN CHARACTERISTICS			
Total capacity:	Total	1500	L
Maximum working pressure:		6	bar
Maximum working temperature:		110	°C
Connections:	eh: side connection	2	" F
	N: side connection	2	" F
	p: upper connection	1	" M
	S: conexión colectores	2	" F
	tm: sensor connections	½	" F
	R: side connection for electric element	2	" F
Energy efficiency:	ErP Class	C	
	Static heat losses acc. to EN12897	156	W
External dimensions:	D: Diameter	1160	mm
	H: Height (without connections)	2320	mm
	Diagonal (without connections)	2593	mm
Packaging dimensions:	Width / Height	1160 x 2320	mm
Weight:	Without packaging / With packaging	311 / 313	kg