



EXTERNAL PROTECTION:

- Shot-blasting to SA 2-1/2
- Anti-corrosion primer
- Polyurethane finish

LARGE DIAMETER series models.

- The size, distribution and distance between connections and other elements can be adapted to meet the requirements of each project.
 - Details of the external surface finish are to be confirmed at the quotation stage.
 - Optional supply of valve sets corresponding to each tank model.
 - The drawing shows tanks for aboveground installation.
- Same capacities for underground installation (please consult).
Outlets and valves: see page 17.

CHARACTERISTICS TABLE

Model Ref.	Rated capacity (litres)	Approx. empty weight (Kg)	(1) Stored propane (Kg)	Total area (m ²)	Minimum discharge of safety valve (m ³ /min. air)		Dimensions (mm)			
					Abovegrd.	Undergrd	A	B	D	I
LP100A-30	101.000	21.110	42.420	147,8	640,8	448,5	15.120	9.000	3.000	2.200
LP125A-30	126.000	25.790	52.920	181,7	759,0	531,3	18.720	11.000	3.000	2.200
LP150A-30	150.800	30.460	63.336	215,7	873,6	611,5	22.320	13.000	3.000	2.200
LP175A-30	175.700	35.140	73.794	249,7	985,0	689,5	25.930	16.000	3.000	2.200
LP150A-35	150.400	32.000	63.168	189,8	786,6	550,6	16.600	11.500	3.500	2.600
LP175A-35	175.400	36.770	73.668	219,0	884,6	619,2	19.260	13.000	3.500	2.600
LP200A-35	200.400	41.540	84.168	248,1	979,8	685,9	21.910	13.900	3.500	2.600
LP250A-35	250.300	51.080	105.126	306,5	1.165,3	815,7	27.200	18.000	3.500	2.600
LP275A-35	275.800	55.940	115.836	336,2	1.257,1	880,0	29.920	20.000	3.500	2.600
LP200A-38	200.800	43.420	84.336	232,7	929,7	650,8	18.780	13.000	3.800	2.750
LP250A-38	249.600	52.920	104.832	285,3	1.098,8	769,1	23.180	14.000	3.800	2.750
LP275A-38	275.700	58.000	115.794	313,4	1.186,8	830,7	25.540	15.000	3.800	2.750
LP300A-38	300.700	62.860	126.294	340,3	1.269,7	888,8	27.790	17.000	3.800	2.750
LP325A-38	325.100	67.610	136.542	366,6	1.349,6	944,7	29.990	20.000	3.800	2.750
LP250A-40	250.500	53.920	105.210	274,5	1.064,6	745,2	21.100	13.000	4.000	3.000
LP275A-40	275.100	58.680	115.542	299,7	1.144,0	800,8	23.100	14.000	4.000	3.000
LP300A-40	299.700	63.440	125.874	324,8	1.222,0	855,4	25.100	15.000	4.000	3.000
LP325A-40	326.000	68.450	136.920	351,3	1.303,2	912,3	27.200	17.000	4.000	3.000
LP350A-40	340.000	71.300	142.800	366,3	1.348,7	944,1	28.400	20.000	4.000	3.000
LP275A-42	276.000	57.880	115.920	288,9	1.110,1	777,1	21.100	13.000	4.200	Without supports
LP300A-42	301.100	62.610	126.462	313,3	1.186,4	830,5	22.950	14.000	4.200	Without supports
LP325A-42	326.300	67.350	137.046	337,8	1.262,0	883,4	24.810	15.000	4.200	Without supports
LP350A-42	340.500	70.030	143.010	351,6	1.304,1	912,9	25.860	16.500	4.200	Without supports
LP400A-42	401.000	81.410	168.420	410,4	1.480,4	1.036,3	30.310	20.000	4.200	Without supports

(1) Propane stored in kg, considering a degree of filling of 85% of the tank and a LPG density of 0.5 kg/l.

A= Aboveground (Underground tanks: please consult us).
(*)Weights for a design pressure of 19 bar.